

# All Electric



OLD VALUES. NEW IDEAS.



A clean running  
pressure washer  
providing powerful,  
environmentally  
safe operation.

## SPECIFICATIONS

### ALL ELECTRIC

MODEL	2148**	3158**	4108**	4208	4258**	4308	108
Gallage*	2 GPM	3 GPM	4 GPM	3.5 GPM	4 GPM	3.5 GPM	100 GPH
Pressure	1400 PSI	1500 PSI	1000 PSI	2000 PSI	2500 PSI	3000 PSI	400 PSI
Pump	Triplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement
Motor	2 HP	3 HP	3 HP	5 HP	7.5 HP	7.5 HP	3/4 HP
Water Heater	Replaceable, 3 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard
Power Requirements	240 V, 3 PH (80 Amps)	240 V, 3 PH (155 Amps) 480 V, 3 PH (77 Amps)	240 V, 3 PH (155 Amps) 480 V, 3 PH (77 Amps)	240 V, 3 PH (155 Amps) 480 V, 3 PH (77 Amps)	240 V, 3 PH (160 Amps) 480 V, 3 PH (80 Amps)	240 V, 3 PH (160 Amps) 480 V, 3 PH (80 Amps)	240 V, 3 PH (155 Amps) 480 V, 3 PH (77 Amps)
Heat Rise	110° F	140° F	100° F	100° F	100° F	100° F	250° F
Wand	Trigger-Standard	Trigger-Standard	Trigger-Standard	Trigger-Standard	Trigger-Standard	Trigger-Standard	Open-Standard
Hose	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'
Chemical	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
Floot Tank	Stainless Steel Floot Controlled	Stainless Steel Floot Controlled	Stainless Steel Floot Controlled	Stainless Steel Floot Controlled	Stainless Steel Floot Controlled	Stainless Steel Floot Controlled	Stainless Steel Floot Controlled
Options	Wheel Kit	Wheel Kit	Wheel Kit	Wheel Kit	Wheel Kit	Wheel Kit	Wheel Kit
Dimensions	34" L, 24" W, 37" H	34" L, 24" W, 37" H	34" L, 24" W, 37" H	34" L, 24" W, 37" H	34" L, 24" W, 37" H	34" L, 24" W, 37" H	34" L, 24" W, 37" H
Weight	335 LBS	375 LBS	375 LBS	375 LBS	385 LBS	385 LBS	360 LBS

### FEATURES

- Triplex, oil bath crankcase pump
- Stainless steel immersion heaters
- Standard temperature control
- 240 volt or 480 volt, 3 phase power
- 1000 PSI to 3000 PSI
- Heavy duty wheel kit (optional)
- Easy grip trigger gun

### ADVANTAGES

- Completely powered by electricity
- Safe where open flame is a problem
- Takes up little space
- Creates minimal noise
- Does not emit smoke
- Operates without fumes of any kind

\*Gallage and pressure may vary  $\pm$  5% due to manufacturing tolerances in components. Specifications subject to change without notice.

\*\*These models available UL approved.

### ENGLISH TO METRIC CONVERSION CHART

1 gallon/minute = 3.78 liters/minute  
 1 horsepower = .746 kilowatts  
 100 PSI = 7.03 Kg/cm<sup>2</sup>  
 1 foot = .3048 meters  
 1 inch = 2.54 centimeters  
 1 pound = .45359 kilograms



OLD VALUES. NEW IDEAS.

Alcester, South Dakota 57001  
 1.800.255.6823 www.alkota.com

