



COBBALT™



Reliable General Pumps™!

1000 PSI @ 2.8 GPM

2000 PSI @ 4.0 GPM

2300 PSI @ 4.8 GPM

2300 PSI @ 6.5 GPM

3000 PSI @ 4.8 GPM

Cold-Water, Belt-Drive, Hot-Water Capable!



COBALT™



Model Number	Motor	HP	VAC / Phase	AMP	Pump	PSI	GPM	Weight	Dimensions*
DC1000	Baldor™	2.0	115 / 1	19	T991	1000	2.8	200 lbs.	30" x 21" x 16"
DC2000	Baldor™	5.0	230 / 1	25	TS1811	2000	4.0	275 lbs.	30" x 21" x 16"
DC2300	Baldor™	7.5	230 / 1	36	TS1811	2300	4.8	325 lbs.	30" x 21" x 16"
DC2365	Baldor™	10	230 / 1	36	TS1819	2300	6.5	325 lbs.	30" x 21" x 16"
DC3000	Baldor™	10	230 - 460 / 3	28/14	TS1021	3000	4.8	325 lbs.	30" x 21" x 16"

*Dimensions represent model without wheels or handle attached.

Standard Features

The Control Panel

- **Four mounting points for the nozzles.**
- **Power on-off switch mounted away from water inlet or outlet, improving safety for the operator.**
- **Includes Hour Meter Display**

The Pump and the Motor

- **General Pumps™ brand Industrial Triplex Pumps.**
- **Dual Belt Drive System connects the pump to the motor.**
- **Quick-Connect downstream (low pressure) detergent injector with detergent & chemical pickup hose.**
- **Baldor® Motors deliver long life.**
- **Includes Thermal Relief Valve.**
- **Includes Over Pressure Relief Valve.**

Factory Installed Options

- **Wall-Mount Kit**
- **Hose Reel Kit**
- **Stainless Steel Cover**

The Frame and Accessories

- **Rugged steel tube frame with durable powder coated finish.**
- **Includes 50' of 3/8" high pressure hose rated for hot water use, trigger gun, and wand.**
- **Includes removable ventilated panel for easy access to the pump & motor.**
- **Dual 13" Pneumatic Tires and compact front swivel wheels give the Cobalt Cold Water a smooth ride around your job site.**



Your DELCO Distributor is:

