

Water Blaster®



ENGINEERED FOR THE PROFESSIONAL TRADE

The Water Blaster® outperforms everything in its class. When power, performance, and reliability are needed, the Water Blaster® is the indisputable winner among professional cleaning contractors. The Water Blaster® dual belt-drive system provides positive and redundant power transfer from the engine to the pump for years of reliable use.

Key Features:

- Belt Drive Engine and Pump System
- HONDA® GX Series Engine with Oil Alert® or SUBARU® EX Series Engine
- Industrial Triplex Plunger Pump
- Adjustable Unloader
- Built-in Chemical Injector
- High Pressure Relief Valve for Operator Safety
- Thermal Relief Valve
- Easy-start Valve
- 50-feet of Abrasion and UV Resistant High Pressure MONSTER HOSE®
- Heavy Duty Powder-Coated Steel Frame
- Heavy Duty steel subframe provides additional support
- Polished Chrome Front and Rear Handles
- 13" Premium Treaded Tires on Aluminum "Mag" Wheels
- Professional Spray Gun & Wand
- Includes 5 Quick Connect Nozzles - 0°, 15°, 25°, 40°, and Chemical Application

TECHNICAL DATA		WB3200	WB3200S	WB4200	WB4200S
FLOW OUTPUT	(gpm)	3.5	3.5	3.5	3.5
PRESSURE RATING	(psi)	3200	3200	4200	4200
MAX INLET TEMP	(°F)	120	120	120	120
ENGINE BRAND		HONDA®	SUBARU®	HONDA®	SUBARU®
ENGINE MODEL		GX270	EX	GX390	EX
ENGINE FUEL		GAS	GAS	GAS	GAS
FUEL CAPACITY	(gallon)	1.6	1.6	1.7	1.7
ENGINE RPM		3400	3400	3400	3400
PUMP RPM		1725	1725	1725	1725
ENGINE-PUMP DRIVE		BELT	BELT	BELT	BELT

DIMENSIONS

LENGTH	(inch)	42	42	42	42
WIDTH	(inch)	26	26	26	26
HEIGHT	(inch)	26	26	26	26
APPROX. WEIGHT	(lbs)	150	150	180	180



www.simpsoncleaning.com