



AVENGER

NATURAL GAS & LIQUID PROPANE



Stationary Design

- **Ideal for permanent in-plant installation and operation**
- **LP or NG Fuel Systems**
- **Single Phase or Three Phase Electric Controls**

Reliable General Pumps™!

- **2000 PSI @ 4.0 GPM**
- **3000 PSI @ 4.0 GPM**
- **3000 PSI @ 5.0 GPM**

Belt Drive Motor-Pump System!



AVENGER

NATURAL GAS & LIQUID PROPANE

Part #	HP / VAC / Phase	Amp Draw	Pump	Fuel	PSI	GPM	BTU / Hr	Weight	Dimensions
9147A	5 / 230 / 1	25	GENERAL	NG	2000	4.0	436,000	625 lbs.	51" x 23" x 48"
9148A	5 / 230 / 1	25	GENERAL	LP	2000	4.0	436,000	625 lbs.	51" x 23" x 48"
9143A	5 / 230 - 460 / 3*	14	GENERAL	NG	2000	4.0	436,000	625 lbs.	51" x 23" x 48"
9144A	5 / 230 - 460 / 3*	14	GENERAL	LP	2000	4.0	436,000	625 lbs.	51" x 23" x 48"
9139A	7.5 / 230 - 460 / 3*	11	GENERAL	NG	3000	4.0	352,000	650 lbs.	51" x 23" x 48"
9140A	7.5 / 230 - 460 / 3*	11	GENERAL	LP	3000	4.0	436,000	650 lbs.	51" x 23" x 48"
9133A	7.5 / 230 - 460 / 3*	14	GENERAL	NG	3000	5.0	469,000	650 lbs.	51" x 23" x 48"
9134A	7.5 / 230 - 460 / 3*	14	GENERAL	LP	3000	5.0	489,000	650 lbs.	51" x 23" x 48"

* These Avenger Models are also available in Single Phase configuration upon request.

Key Features

The Control Panel

- **Centralized location for all controls.**
- **Hour meter standard on all models.**
- **24VDC Electrical controls.**

The Pump and the Motor

- **General Pumps™ brand Industrial Triplex Pumps.**
- **Dual Belt Drive System provides redundant power to the pump.**
- **Built-in upstream (high pressure) detergent injector with detergent & chemical pickup hose and chemical metering valve.**
- **Automatic System Shutdown after 4.5 minutes of inactivity.**
- **Options include thermostatic control and 24VAC Control System.**

Factory Installed Options

- **Thermostatic Control**
- **Remote Control (Wire loop not provided)**
- **Additional Remote Control**
- **Stainless Steel Wrapper**
- **Stainless Steel Control Panel**
- **Oil fired Burner (replaces NG/LP) with fuel tank**

The Hot Water System

- **Clean burning, fuel efficient vertical combustion chamber includes 12" draft diverter.**
- **Full 140° F heat rise, up to a high limit of 230° F.**
- **NG or LP models available.**
- **Electronic Ignition**
- **Adjustable Auto-Stop Timer.**

The Frame and Accessories

- **Protective shroud covers the belts and pulleys from area debris.**
- **Motor and pump system are easily accessible for service or repair.**
- **Includes 50' of 3/8" high pressure hose rated for hot water use, trigger gun, wand, and four QC Nozzles.**
- **Options include remote control and stainless steel wrapper / panel.**

Your DELCO Distributor is:

