

# Delco ELIMINATOR

### NATURAL GAS & LIQUID PROPANE



**Stationary Design** 

- Ideal for permanent in-plant installation and operation
- LP or NG Fuel Systems
- Rugged Baldor® Motors

### Reliable General Pumps...!

- 2000 PSI @ 4.0 GPM
- 3000 PSI @ 4.0 GPM
- 3000 PSI @ 5.0 GPM

**Belt Drive Motor-Pump System!** 



### ELIVINATOR

#### NATURAL GAS & LIQUID PROPANE

Part #	HP / VAC / Phase	Amp Dra	w Pump	Fuel	PSI	GPM	BTU / Hr	Weight	Dimensions
60331	5/230/1	28	TS1811	NG	2000	4.0	440,000	725 lbs.	50" x 26" x 50"
60332	5/230/1	25	TS1811	LP	2000	4.0	440,000	725 lbs.	50" x 26" x 50"
60333	7.5 / 230 / 1	36	TS1811	NG	3000	4.0	440,000	725 lbs.	50" x 26" x 50"
60334	7.5 / 230 / 1	36	TS1811	LP	3000	4.0	440,000	725 lbs.	50" x 26" x 50"
60335	10 / 230 - 460 / 3	30 - 14	TS1021	NG	3000	5.0	440,000	725 lbs.	50" x 26" x 50"
60336	10 / 230 - 460 / 3	30 - 14	TS1021	LP	3000	5.0	440,000	725 lbs.	50" x 26" x 50"

## **Key Features**

#### The Control Panel

- Centralized location for all controls.
- · Hour meter standard on all models.
- 24V Electrical controls.
- Hinged Control Panel allows easy access to electronics & wiring.

#### The Pump and the Motor

- General Pumps<sup>™</sup> brand Industrial Triplex Pumps.
- · Rugged Baldor® Motors.
- Dual Belt Drive System provides redundent power to the pump.
- Automatic System Shutdown after
  4.5 minutes of inactivity.
- Downstream Chemical Injection.

#### The Hot Water System

- Clean burning, fuel efficient vertical combustion chamber.
- Full 140° F heat rise, up to a high limit of 230° F.
- NG or LP models available.
- Electronic Ignition
- Adjustable Auto-Stop Timer.
- Thermostat Control System.
- 5 year warranty on Burner Coil.

#### The Frame and Accessories

- Protective shroud covers the belts and pulleys from area debris.
- Motor and pump system are easily accessible for service or repair.
- Includes 50' of 3/8" high pressure hose rated for hot water use, trigger gun, wand, and four QC Nozzles.

#### **Factory Installed Options**

- Hose Reel
- Remote Control (Wire loop not provided)
- Steam Option available
- 10-inch Draft Diverter
- L.P. Burner Available

 Built-in downstream (high pressure) detergent injector with detergent & chemical pickup hose and chemical metering valve.

