



A Division of Blast Off Cleaning Equipment LLC

**FULL LINE OF FIRE EXTINGUISHERS
REFILL & REFURBISH ON-SITE
FIRST AID • SAFETY LIGHTING • EYE WASH STATIONS
SALES • INSTALLATION • SERVICE**

724-439-9120 • 1-800-356-9274

394 Old Pittsburgh Road • Uniontown, PA 15401

ABC DRY CHEMICAL HAND HELD STORED PRESSURE FIRE EXTINGUISHERS

FEATURES:

- Monoammonium Phosphate based dry chemical agent.
- Rated for use on “A”, “B”, and “C” class fires. Provides the widest, most practical range of fire protection.
- Rechargeable
- Steel cylinders with a baked-on polyester enamel coating stand up to harsh environments.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 Standards
- Optional brass valves on some units. 30 lb. unit has brass valve only

TYPICAL USES: Offices, warehouses, woodworking areas, farms, general public assembly areas, and homes. The ABC extinguisher is not recommended for use on sensitive electronic equipment or aircraft structure.



Model	2.5 ABC V/B	5 ABC	5 ABC V/B	10 TALL ABC	10S ABC	20S ABC	30S ABC
Part # Alum. Valve	13315	10914	25614	11340	11310	12120	N/A
Part # Brass Valve	N/A	10915	25615	11341	N/A	12121	12905
Agent Capacity	2.5 lb. (1.13 kg)	5 lb. (2.27 kg)		10 lb. (4.54 kg)		20 lb. (9.07 kg)	30 lb. (13.6 kg)
UL Rating	1A-10B:C	3A-40B:C		4A-80B:C	4A-60B:C	20A-120B:C	20A-160B:C
Discharge Time	9 sec	14 sec		22 sec	18 sec	26 sec	32 sec
Range (ft/m)	9-15 / 2.7-4.6	12-18 / 3.7-5.5		15-21 / 4.6-6.4		25-30 / 7.6-9.1	
Operating Pressure	100 psi (689 kPa)	195 psi (1344 kPa)					
Bracket	Vehicle	Wall	Vehicle	Wall			
USCG Approval	Type B:C Size I	Type A Size II Type B:C Size I		Type A Size II Type B:C Size II		Type A Size II Type B:C Size III	Type A Size II Type B:C Size IV
Ship Wt.	5.5 lbs. (2.5 kg)	10 lbs. (4.5 kg)	10.25 lbs. (4.7 kg)	18.25 lbs. (8.3 kg)	18.75 lbs. (8.6 kg)	33.5 lbs. (15.2 kg)	52.25 lbs. (23.7 kg)
Height	14.75 in (37.5 cm)	16.375 in (41.6 cm)		21 in (53.3 cm)	16.75 in (42.5 cm)	21.25 in (53.8 cm)	27.375 in (69.4 cm)
Width	4.875 in (12.4 cm)	7.25 in (18.4 cm)		7.75 in (19.7 cm)	8.25 in (21 cm)	8.75 in (22.2 cm)	
Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)		5.125 in (13 cm)	6 in (15.2 cm)	7.5 in (19.1 cm)	

STANDARD DRY CHEMICAL HAND HELD STORED PRESSURE FIRE EXTINGUISHERS

FEATURES:

- Sodium Bicarbonate based dry chemical agent.
- Rated for use on “B” and “C” Class fires.
- Rechargeable
- Steel cylinder with a baked-on polyester enamel coating stands up to harsh environments.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 Standards.

TYPICAL USES: Kitchens, garages, boats, vehicles, and extinguisher use training. The Standard extinguisher is not recommended for use on sensitive electronic equipment.



Model	2.5 STD V/B	5.5 STD	5.5 STD V/B	10 STD	20S STD
Part # Aluminum Valve	13415	11014	13514	11840	12220
Agent Capacity	2.5 lbs. (1.13 kg)	5.5 lbs. (2.50 kg)		10 lbs. (4.54 kg)	20 lbs. (9.07 kg)
UL Rating	10 B:C	40 B:C			120 B:C
Discharge Time	9 seconds	14 seconds			26 seconds
Range	9-15 ft (2.7-4.6 m)	12-18 ft (3.7-5.5 m)		15-21 ft (4.6-6.4 m)	
Operating Pressure	100 psi (689 kPa)	195 psi (1344 kPa)			
Bracket	Vehicle	Wall	Vehicle	Wall	
USCG Approval	Type B:C Size I			Type B:C Size II	Type B:C Size III
Ship Wt.	5.5 lbs. (2.5 kg)	10.5 lbs. (4.8 kg)	10.75 lbs. (4.9 kg)	18.25 lbs. (8.3 kg)	33.5 lbs. (15.2 kg)
Height	14.75 in (37.5 cm)	16.375 in (41.6 cm)		21 in (53.3 cm)	21.25 in (53.8 cm)
Width	4.875 in (12.4 cm)	7.25 in (18.4 cm)		7.75 in (19.7 cm)	8.75 in (22.2 cm)
Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)		5.125 in (13 cm)	7.5 in (19.1 cm)

PURPLE K DRY CHEMICAL HAND HELD STORED PRESSURE FIRE EXTINGUISHERS

FEATURES:

- Potassium Bicarbonate based dry chemical agent.
- Rated for use on “B”, and “C” class fires. Most effective dry chemical agent for Class B fires
- Rechargeable
- Steel cylinder with a baked-on polyester enamel coating stands up to harsh environments.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 Standards
- Optional brass valves on some units. 30 lb. unit has brass valve exclusively.

TYPICAL USES: Garages, service bays, boats, vehicles, fuel storage and transfer areas. The Purple K extinguisher is not recommended for use on sensitive electronic equipment.



Model	2.5 PK V/B	5 PK	5 PK V/B	10 PK	20S PK	30S PK
Part # Alum. Valve	13515	11214	25914	11740	12620	N/A
Part # Brass Valve	N/A	N/A	N/A	N/A	12621	12805
Agent Capacity	2.5 lbs (1.13 kg)	5 lbs. (2.27 kg)		10 lbs (4.54 kg)	20 lbs. (9.07 kg)	30 lbs. (13.6 kg)
UL Rating	10 B:C	20 B:C		80 B:C	120 B:C	160 B:C
Discharge Time	9 seconds			22 seconds	26 seconds	32 seconds
Range	9-15 ft (2.7-4.6 m)	12-18 ft (3.7-5.5 m)		15-21 ft (4.6-6.4 m)		25-30 ft (7.6-9.1 m)
Operating Pressure	100 psi (689 kPa)	195 psi (1344 kPa)				
Bracket	Vehicle	Wall	Vehicle	Wall		
USCG Approval	Type B:C Size I			Type B:C Size II	Type B:C Size III	Type B:C Size IV
Ship Wt.	5.5 lbs (2.49 kg)	10 lbs. (4.5 kg)	10.25 lbs. (4.6 kg)	18.25 lbs. (8.3 kg)	33.5 lbs. (15.2 kg)	52.25 lbs. (23.7 kg)
Height	14.75 in (37.5 cm)	16.375 in (41.6 cm)		21 in (53.3 cm)	21.25 in (53.8 cm)	27.375 lbs. (69.4 cm)

Width	4.875 in (12.4 cm)	7.25 in (18.4 cm)	7.75 in (19.7 cm)	8.75 in (22.2 cm)
Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)	5.125 in (13 cm)	7.5 in (19.1 cm)

HALOTRON HAND HELD AND WHEELED STORED PRESSURE FIRE EXTINGUISHERS

FEATURES:

- Residue-free Hydrochlorofluorocarbon gas agent pressurized with argon.
- Excellent replacement for Halon 1211 extinguishers.
- Rechargeable steel cylinders with baked-on polyester enamel coating that stands up to harsh environments.
- Wheeled units have DOT approved 4BW240 cylinders, rugged frames, and semi-pneumatic tires.
- All units are manufactured to ANSI/UL 2129 and ANSI/UL 711 Standards.
- Optional chrome-plated brass valves on some units (standard on Wheeled Extinguishers).

TYPICAL USES: Computer rooms, telephone switch rooms, data storage areas, boats, and flight lines.



Model	2.5F	2.5F V/B	2.5H	2.5H V/B	5F	5F V/B	5H	5H V/B	11	15	
Part # Alum. Valve	70258	70251	70259	70256	70510	70550	75550	75555	71100	71550	
Part # Brass Valve	Not Available				70511	70551	75551	75556	71101	71551	
Agent Capacity	2.5 lbs (1.13 kg)				5 lbs. (2.27 kg)		5.5 lbs. (2.49 kg)		11 lbs. (5 kg)	15.5 lbs. (7.03 kg)	
UL Rating	2B:C				5B:C				1A-10B:C	2A-10B:C	
Discharge Time	9 seconds									13 seconds	
Range	6-10 ft (1.8-3 m)				9-15 ft (2.7-4.5 m)				12-18 ft (3.7-5.5 m)		
Operating Pressure	100 psi (689 kPa)									125 psi (862 kPa)	
Bracket	Wall	Vehicle	Wall	Vehicle	Wall	Vehicle	Wall	Vehicle	Wall		
USCG Approval	Not Applicable				Type B:C Size I					Type B:C Size II	
Ship Wt.	5.25 lbs (2.4 kg)	5.5 lbs. (2.49 kg)		5.75 lbs (2.6 kg)	9.25 lbs. (4.2 kg)	9.5 lbs. (4.3kg)	10 lbs. (4.5 kg)	10.25 lbs. (4.7 kg)	21.25 lbs. (9.6 kg)	25.75 lbs. (11.7 kg)	
Height	13.375 in (34 cm)				16.375 in (41.6 cm)				17.5 in (44.5 cm)		
Width	5.625 in (14.3 cm)		6.75 in (17.1 cm)		6.5 in (16.5 cm)	7.25 in (18.4 cm)	6.5 in (16.5 cm)	7.25 in (18.4 cm)	8.625 in (21.9 cm)		
Diameter	3.375 in (8.6 cm)				4.25 in (10.8 cm)				7 in (17.8 cm)		

Wheeled Extinguishers

Model	Part #	Capacity	UL Rating	Discharge Time	Range	Unit Height x Width x Depth	Hose Diameter x Length	Ship Weight
W-65	76500	65 lbs (29.5 kg)	4A-40B:C	17 seconds	15-25 ft (4.6-7.6 m)	50 x 24 x 41.5 in (127 x 61 x 105 cm)	.75 in x 25 ft (1.9 cm x 7.6 m)	300 lbs (136 kg)
W-150	71500	150 lbs (68 kg)	10A- 80B:C	23 seconds	23-36 ft (7-10.7 m)	62 x 24 x 41.5 in (157.5 x 61 x 105 cm)	1 in x 40 ft (2.5 cm x 12.2 m)	480 lbs (218 kg)

CARBON DIOXIDE HAND-HELD AND WHEELED FIRE EXTINGUISHERS

FEATURES:

- Residue-free carbon dioxide gas extinguishing agent.
- Hand-held units use aluminum cylinders with a baked-on polyester enamel coating to withstand harsh environments.
- Wheeled units are constructed with spun steel cylinders, rugged frames, and pneumatic tires and are designed to be easily operated by one person.
- All units manufactured to ANSI/UL 154 and ANSI/UL 711 Standards and use DOT compliant cylinders.
- Plated brass valves on both hand-held and wheeled units.
- Optional tow loops offered on the wheeled extinguishers.

TYPICAL USES: Refineries, shipboard, laboratories, construction sites, chemical plants, and manufacturing facilities.



Hand-Held Extinguishers				
Model	5CD	10CD	15CD	20CD
Part Number	45100	45600	46100	46600
Agent Capacity	5 lbs. (2.27 kg)	10 lbs. (4.54 kg)	15 lbs. (6.80 kg)	20 lbs. (9.07 kg)
UL Rating	5B:C	10B:C		
Discharge Time	8 seconds	10 seconds	15 seconds	20 seconds
Range	4-8 ft (1.2-2.4 m)			
Bracket	Wall			
USCG Approval	Type B:C Size I		Type B:C Size II	
Ship Wt.	13.75 lbs. (6.3 kg)	27.75 lbs. (12.6 kg)	37.75 lbs. (17.1 kg)	49.0 lbs. (22.2 kg)
Height	17.375 in (44.1 cm)	19.75 in (50.2 cm)	26.375 in. (67 cm)	26.875 in (68.2 cm)
Width	8.25 in (21 cm)	12 in (30.5 cm)		13 in (33 cm)
Diameter	5.25 in (13.3 cm)	6.89 in (17.5 cm)		8 in (20.3 cm)

Wheeled Extinguishers								
Model	Part #	Capacity	UL Rating	Discharge Time	Range	Unit Height x Width x Depth	Hose Dia x Length	Ship Weight
C-50-SE	35050	50 lbs. (22.68 kg)	20B:C	40 seconds	15 ft (4.6m)	60 x 30 x 21 in (152.4 x 76.2 x 53.3 cm)	1 in x 15 ft (2.5 cm x 4.56 m)	250 lbs. (113.4 kg)
C-100-SE	35100	100 lbs. (45.36 kg)		80 seconds		65 x 30 x 21 in (165.1 x 76.2 x 53.3 cm)	1 in x 40 ft (2.5 cm x 12.2 m)	390 lbs. (176.9 kg)

AUTOMATIC SPOT PROTECTION

FEATURES:

- Designed to provide supplemental protection suitable for some local and total flood applications.
- Two mount styles available, charged with multipurpose dry chemical (ABC) or clean agent Halotron™.
- The cylinders are constructed and tested to the same engineering standards as our portable extinguishers.
- These units are not Underwriters Laboratories Listed and are not intended for use in lieu of an engineered system. They are not to be multiple mounted.



VERTICAL MOUNT STYLE

Agent	Multipurpose ABC Dry Chemical				Halotron™	
Part No.	80250	80501	81001	82001	87100	87200
Capacity (lb./kg)	2.5 lbs/ 1.13 kg	5 lbs/ 2.3 kg	10 lbs/ 4.5 kg	20 lbs/ 9.1 kg	18 lbs/ 8.2 kg	25 lbs/ 11.3 kg
Ship Wt. (lb./kg)	4 lbs/ 1.8 kg	11 lbs/ 5.0 kg	19 lbs/ 8.6 kg	36 lbs/ 16.3 kg	29 lbs/ 13.2 kg	42 lbs/ 19.0 kg
Operating Pressure	100 psi (689 kPa)		195 psi (1344 kPa)		100 psi (689 kPa)	
Length	15.25 in	17.25 in	17.625 in	21.875 in	17.875 in	21.875 in
Diameter	3.375 in	4.25 in	6.0 in	7.5 in	7.0 in	7.5 in
Max Total Flood-Volume	120 cu ft	180 cu ft	1300 cu ft	2184 cu ft	500 cu ft	700 cu ft
Max Total Flood-Height above Hazard	7.5 ft		13 ft	14 ft	8 ft	10 ft
Local Application Coverage Areas	4 ft x 4 ft	4 ft x 6 ft	10 ft x 10 ft	12 ft x 13 ft	4 ft x 4 ft	6 ft x 6 ft
Max Local Application- Height Above Hazard = 4 feet for all models						

HORIZONTAL MOUNT STYLE

Agent	Multipurpose ABC dry chemical				Halotron™	
Part No.	80251	80521	81021	82021	87105	87205
Capacity (lb./kg)	2.5 lbs/ 1.13 kg	5 lbs/ 2.3 kg	10 lbs/ 4.5 kg	20 lbs/ 9.1 kg	18 lbs/ 8.2 kg	25 lbs/11.3 kg
Ship Wt. (lb./kg)	4 lbs/ 1.8 kg	11 lbs/ 5.0 kg	19 lbs/ 8.6 kg	36 lbs/ 16.3 kg	29 lbs/ 13.2 kg	42 lbs/ 19.0 kg
Operating Pressure	100 psi (689 kPa)		195 psi (1344 kPa)		100 psi (689 kPa)	
Length	14.25 in	17.25 in	20.875 in	21.875 in	17.875 in	21.875 in
Diameter	3.375 in	4.25 in	5.125 in	7.5 in	7.0 in	7.5 in

Max Total Flood-Volume	120 cu ft	180 cu ft	1300 cu ft	2184 cu ft	500 cu ft	700 cu ft
Max Total Flood-Height above Hazard	7.5 ft		13 ft	14 ft	8 ft	10 ft
Local Application Coverage Areas	4 ft x 4 ft	4 ft x 6 ft	10 ft x 10 ft	12 ft x 13 ft	4 ft x 4 ft	6 ft x 6 ft
Mounting Bracket	700287	700270	700226	700229	700228	700229
Max Local Application- Height Above Hazard = 4 feet for all models						

DRY CHEMICAL WHEELED FIRE EXTINGUISHERS

FEATURES:

- Three choices in dry chemical agents are available to suit your particular fire protection needs: Monoammonium Phosphate (ABC), Sodium Bicarbonate (Standard), and Potassium Bicarbonate (Purple K).
- The ABC extinguisher is rated for use on “A”, “B”, and “C” class fires, providing the widest, most practical range of fire protection. The Standard and Purple K extinguishers are rated for use on B:C classes of fires.
- Designed for one-man operation. Easily transported through doorways and over rough terrain.
- All models are also available as stationary units.
- Every model is rechargeable.
- Rugged steel cylinders and frames with baked-on polyester enamel coatings stand up to harsh environments.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 Standards.
- Plated brass cylinder valves and hose valve assemblies.
- All pressurized cylinders are DOT approved. Extinguishers part numbered 30010, 30110, 30030, 30310, & 31210 are USCG approved.

TYPICAL USES:

Offshore rigs, ship docks, refineries, chemical plants, aircraft ramps, remote construction sites, large laboratories, processing plants, storage and loading areas. These extinguishers are not recommended for use on sensitive electronic equipment.



WHEELED EXTINGUISHER PHYSICAL ATTRIBUTES							
MODEL	PART NO.	SHIP WEIGHT	HEIGHT	WIDTH	DEPTH	HOSE LENGTH x DIA	WHEEL DIAMETER
A-50-SP	30010	193 lbs.	47 inches	24 inches	26.5 inches	25 ft. x .50 in	12.3 x 3.5 in
K-50-SP	30030	(88 kg)	(119 cm)	(61 cm)	(67 cm)	(7.6 m x 1.3 cm)	(31.3 x 8.9 cm)
A-150-SP	30110	343 lbs.	51 inches	26 inches	38 inches	50 ft x .75 in	16 x 4 in

K-150-SP	30310	(156 kg)	(128 cm)	(66 cm)	(96.5 cm)	(15.2 m x 1.9 cm)	(40.6 x 10.2 cm)				
A-150-RG	31120	413 lbs.	50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)						
K-150-RG	31320	(188 kg)									
S-150-RG	31220	438 lbs. (199 kg)	55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)		36 x 2.5 in (91.4 x 6.4 cm) * Steel Wheels ** Steel wheels with rubber tread				
A-150-RG	31140*	448 lbs. (204 kg)									
	31150**										
K-150-RG	31340*	473 lbs. (215 kg)	50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)		50 ft x 1 in (15.2 m x 2.5 cm)	16 x 4 in (40.6 x 10.2 cm)			
	31350**										
S-150-RG	31240*	370 lbs. (168 kg)									
	31250**										
A-150-PT	31110	345 lbs.				58 inches (147 cm)		36 inches (91.4 cm)	48 inches (122 cm)	36 x 2.5 in (91.4 x 6.4 cm) * Steel Wheels ** Steel wheels with rubber tread	
K-150-PT	31310	(157 kg)									
S-150-PT	31210	(168 kg)									
A-350-RG	32120*	810 lbs. (368 kg)				58 inches (147 cm)		36 inches (91.4 cm)	48 inches (122 cm)	50 ft x 1 in (15.2 m x 2.5 cm)	36 x 2.5 in (91.4 x 6.4 cm) * Steel Wheels ** Steel wheels with rubber tread
	32140**										
K-350-RG	32320*	860 lbs. (391 kg)									
	32340**										
S-350-RG	32220*	700 lbs. (318 kg)	58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)		50 ft x 1 in (15.2 m x 2.5 cm)				36 x 2.5 in (91.4 x 6.4 cm) * Steel Wheels ** Steel wheels with rubber tread
	32240**										
A-350-PT	32110*	750 lbs. (341 kg)									
	32130**										
K-350-PT	32310*	750 lbs. (341 kg)									58 inches (147 cm)
	32330**										
S-350-PT	32210*	750 lbs. (341 kg)									
	32230**										

ABC WHEELED EXTINGUISHER PERFORMANCE SPECIFICATIONS					
MODEL	PART NO.	AGENT CAPACITY	UL RATING	DISCHARGE TIME	DISCHARGE RANGE
A-50-SP	30010	50 lbs. (22.7 kg)	30A-160B:C	35 seconds	25-35 ft (7.6-10.7 m)
A-150-SP	30110	125 lbs. (56.7 kg)	40A-240B:C	47 seconds	30-40 ft (9.1-12.2 m)
A-150-RG	31120			43 seconds	
	31140				
	31150				
A-150-PT	31110	45 seconds			
A-350-RG	32120	300 lbs. (136 kg)	40A-320B:C	53 seconds	
	32140			57 seconds	
A-350-PT	32110				
	32130				

PURPLE K WHEELED EXTINGUISHER PERFORMANCE SPECIFICATIONS					
MODEL	PART NO.	AGENT CAPACITY	UL RATING	DISCHARGE TIME	DISCHARGE RANGE
K-50-SP	30030	50 lbs. (22.7 kg)	160 B:C	34 seconds	25-35 ft (7.6-10.7 m)
K-150-SP	30310	125 lbs. (56.7 kg)	320B:C	54 seconds	30-40 ft (9.1-12.2 m)
K-150-RG	31320			57 seconds	
	31340				
	31350				
K-150-PT	31310	54 seconds			
K-350-RG	32320	300 lbs. (136 kg)	320B:C	56 seconds	
	32340			58 seconds	
K-350-PT	32310				
	32330				

STANDARD WHEELED EXTINGUISHER PERFORMANCE SPECIFICATIONS					
MODEL	PART NO.	AGENT CAPACITY	UL RATING	DISCHARGE TIME	DISCHARGE RANGE
S-150-RG	31220	150 lbs. (68 kg)	240B:C	48 seconds	30-40 ft (9.1-12.2 m)
	31240				
	31250				
S-150-PT	31210	43 seconds			
S-350-RG	32220	350 lbs. (159 kg)	320B:C	59 seconds	
	32240			50 seconds	
S-350-PT	32210				
		32230			

SPECIALTY FIRE EXTINGUISHERS

WET CHEMICAL – CLASS K

- Contains a blend of Potassium Acetate and Potassium Citrate that is extremely effective in suppressing high temperature fires fueled by the unsaturated cooking oils used in today’s restaurant appliances. The agent is applied by a misting discharge nozzle that prevents the splashing and spreading of the oils. This extinguisher is designed to complement existing pre-engineered hood systems. Also carries an “A” Rating.
- Manufactured to ANSI/UL 8 and ANSI/UL 711 Standards.



Model	WC-6 Liter
Part #	50006
Agent Capacity	6 Liter (1.59 gallons)
UL Rating	1-A:K (Tested to extinguish one 18" X 24" fryer)
Discharge Time	54 seconds
Operating Pressure	100 psi (689 kPa)
Bracket	Wall
Ship Wt.	22 lbs. (10 kg)
Height	19.25 inches (48.9 cm)
Width (including hose)	9 inches (22.9 cm)
Cylinder Diameter	7 inches (17.8 cm)
Construction	Stainless steel cylinder with plated brass valve

WATER

- Uses water as the extinguishing agent. This economical and environmentally friendly extinguisher is ideal for schools, theaters, retail storerooms, and anywhere Class A hazards exist.
- Manufactured to ANSI/UL 8 and ANSI/UL 711 Standards.



Model	500
Part #	50000
Agent Capacity	2.5 gallon (9.6 liters)
UL Rating	2A
Discharge Time	50 seconds
Operating Pressure	100 psi (689 kPa)
Bracket	Wall
Ship Wt. (empty)	7.75 lbs. (3.5 kg)
Height	24.5 inches (62.2 cm)
Width (including hose)	9 inches (22.9 cm)
Cylinder Diameter	7 inches (17.8 cm)
Construction	Stainless steel cylinder with plated brass valve

WATER MIST

- Uses deionized water as the extinguishing agent. The unique misting nozzle creates a fine water spray that improves the cooling and soaking characteristics of the agent and limits the scattering of burning material. This extinguisher is the right choice for Class A fires where there is a potential for Class C (electrical) safety hazards. Ideal for hospitals, clean rooms, and telecom facilities. The non-magnetic properties of the extinguisher make it perfect for use in proximity to MRI equipment.
- Manufactured to ANSI/UL 8 and ANSI/UL 711 Standards.



Model	WM250
Part #	51000
Agent Capacity	2.5 gallon (9.6 liters)
UL Rating	2A:C
Discharge Time	73 seconds
Operating Pressure	100 psi (689 kPa)
Bracket	Wall
Ship Wt.	29.5 lbs. (13.4 kg)
Height	28 inches (71.1 cm)
Width (including hose)	14 in (35.6 cm)
Cylinder Diameter	7 inches (17.8 cm)
Construction	Stainless steel cylinder with plated brass valve

COMBUSTIBLE METALS – CLASS D

- Specially designed for use on combustible metals fires, this extinguisher features a discharge assembly that keeps the operator at a safe distance while providing accurate application of the agent on the fire. From the heat of the fire, the sodium chloride based agent forms a crust to exclude air from the burning material.
- Manufactured to Factory Mutual standards.



Model	30D
Part #	52100
Agent Capacity	30 lbs. (13.6 kg)
FM Rating	D
Discharge Time	28 seconds
Operating Pressure	195 psi (1344 kPa)
Bracket	Wall
Ship Wt.	55 lbs. (24.95 kg)
Height (with hose)	33 inches (83.8 cm)
Width (with hose)	16 inches (40.6 cm)
Cylinder Diameter	8 inches (20.3 cm)
Construction	Steel Cylinder

MOUNTING HARDWARE

The charts below show the corresponding mounting hardware for the extinguishers.

MARINE/VEHICLE BRACKETS



700287



700270



700260



700430



700226, 700228, 700229, 700230

Part No.	Model	Typical Extinguisher Sizes Used For	Reference Diameter
700287	A-2	All 2.5 lb. dry chemical and Halotron™	3.375 in.
700270	A-6	All 5 lb. & 5.5 lb. dry chemical and Halotron™	4.25 in.
700260	B-6	All 5 lb. & 5.5 lb. dry chemical and Halotron™	4.25 in.
700430	B-12	10 Tall dry chemical	5.125 in.
700226	809	10 Tall dry chemical and 5 lb. CO ²	5.0 in. – 5.25 in.
700228	810	10 lb. & 15 lb. CO ² , 11 lb. & 15 lb. Halotron	6.5 in. – 7.25 in.
700229	811	20S lb. and 30S lb. dry chemical, 20 lb. CO ² , Class D	7.0 in. – 8.0 in.
700230	812	10S dry chemical	6.0 in. – 6.25 in.

WALL HOOKS



700202



700203



700204



700247



700249



900935, 900937

Part No.	Typical Extinguisher Sizes Used For	Reference Diameter
700202	2.5 lb., 5 lb., and 5.5 lb. dry chemical and Halotron™	3.25 in. – 4.25 in.
700203	10 Tall & 5 lb. CO ₂	4.75 in. – 5.5 in.
700204	10 Short dry chemical	5.0 in. – 6.5 in.
700247	20 Short & 30 Short dry chemical, 10 & 15 lb. CO ₂ , and 11 & 15 lb. Halotron™	6.75 in. – 7.5 in.
700249	20 lb. CO ₂	7.5 in. – 8.0 in.
900935	Wet Chemical and Water	7.0 in.
900937 (Stainless Steel)	Water Mist	7.0 in.